

# Ururu streamer technology air purifier

MCK55W



Humidification



Flash Streamer

## Humidification and air purification in one

- › Humidification and purification in one
- › Pure air thanks to air purification technologies
- › Catches fine particles of dust
- › Powerful suction and whisper quiet
- › New stylish and compact design

MCK55W



MCK55W

Indoor Unit				MCK	55W
Application					Floor standing type
Applicable room area				m <sup>2</sup>	41 (1) / 82 (2) / 320 (3)
Dimensions	Unit	HeightxWidthxDepth		mm	700 x270 x270
Weight	Unit			kg	9.5
Casing	Colour				White
Fan	Type				Multi Blade Fan (Sirocco fan)
	Air flow rate	Air purifying operation	Silent/Low/Medium/Turbo	m <sup>3</sup> /h	54 /120 /192 /330
		Humidifying operation	Silent/Low/Medium/Turbo	m <sup>3</sup> /h	102 /144 /192 /330
Sound pressure level	Air purifying operation	Silent/Low/Medium/Turbo		dBA	19.0 /29.0 /39.0 /53.0
	Humidifying operation	Silent/Low/Medium/Turbo		dBA	25.0 /33.0 /39.0 /53.0
Humidifying operation	Power input	Silent/L/M/Turbo		kW	0.011 /0.014 /0.019 /0.058
	Humidification	Silent/Low/Medium/Turbo		ml/h	200 /240 /300 /500
	Water tank capacity			l	2.7
Air purifying operation	Power input	Silent/L/M/Turbo		kW	0.007 /0.010 /0.017 /0.056
Deodorizing method					Flash streamer + Deodorizing catalyst
Dust collecting method					Electrostatic HEPA filter
Air filter	Type				Polyethylene terephthalate net
Sign	Item	01	Dust: 3 stages / Odour: 3 stages / Anti-pollen mode / Water supply lamp / Child proof lock lamp / ON/OFF lamp / Streamer lamp / Econo mode / MOIST mode / AUTO FAN mode / PM 2.5 sensor lamp: 3 stages / Humildity monitor lamp: 5 stages / Humildity setting: Low/Standard/High / Airflow rate: Quiet/Low/Standard/Turbo / Humidity on/off		
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/60/220-240/220-230	
Type				Humidifying air purifier	

(1) The applicable room area is appropriate for operating the unit of maximum fan speed (HH). Applicable room area indicates the space where a certain amount of dust particles can be removed in 30 minutes. (JEM 1467) | (2) Converted to NRCC standards from test values in accordance with JEM1467. | (3) Converted to CADR standards from test values in accordance with JEM1467. | Humidification amount changes in accordance with indoor and outdoor temperature and humidity. Measurement condition: 20°C in temperature, 30% in humidity. | Operating sound levels are the average of values measured at 1m away from the front, left, right and top of the unit. (These are equal to the values in an anechoic chamber) | Electrostatic HEPA filter and humidifying filters are attached in the unit.

